

50W & 80W Architectural LED Wall Pack

Lightstat's die-cast aluminum architectural LED wall pack provides a modern look to any building exterior. The superior performance provides a bright, safe environment and is ideal for illuminating stairways, pathways and building exteriors.

KEY FEATURES

ILLUMINATION:

- CREE CXA series LED
- Available in 4000K and 5000K color temperatures

ELECTRICAL:

- Universal 100VAC-277VAC
- 87% Driver efficiency
- Power factor ≥0.9
- CRI: >80
- 50,000 Hour rated lamp life

MOUNTING:

- · Back plate wall mounting bracket standard
- Square Arm or Slip Fitter mounting options are also available

HOUSING:

- Die-cast aluminum housing with durable dark bronze
 powder coat finish
- Tempered glass light cover

WARRANTY/LISTING:

- Tested to UL1598, UL8750, & IEC60598 safety standards
- DLC approved
- *5 year warranty on all electronics and housing
- cULus listed for wet locations (-4°F–104°F)
- IP65 Rated

ORDERING INFORMATION

Example: MODEL-WATTAGE-COLOR TEMP-OPTIONS i.e., "AWP-50W-5K-PC2-SF"


MODEL	WATTAGE	COLOR TEMP	OPTIONS	
AWP	50W	4K	PC1	120V Photocell
	80W	5K	PC2	277V Photocell
			AM	Square Arm
			SF	Slip Fitter
			NO	No Options
			•	•



*Warranty does not apply to installation errors, natural disasters, and/or abuse.

Wattage	Lumens	No.of LEDs
50W	4363	3
80W	7371	3

DIMENSIONS:



MOUNTING OPTIONS:



