

Compact Wet/ Cold Location Exit Sign



KEY FEATURES

ILLUMINATION:

• Ultra bright, energy efficient, Red or Green LEDs

ELECTRICAL:

- Dual 120/277VAC
- Unique bi-color LED indicator light alerts occupant on battery condition (Green-normal, Red-check battery)
- 4.8V long life, maintenance-free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours

MOUNTING:

- · Polycarbonate mounting canopy included for top or end mount
- Universal K/O pattern on back plate for wall mount

HOUSING:

- 5VA flame retardant, UV-stabilized polycarbonate in white, black or gray finish
- High-impact resistant, UV-stabilized polycarbonate clear lens
- Corrosion-resistant enclosure with engineering grade silicone gasket
- Top and side K/O's provided for conduit feed applications
- Snap-out chevron directional indicators


OPTIONS:

- SD: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes
- 2C: Dual circuit option on the AC-only unit enables it to be connected to two different (one acting as a back-up to the other) supplies at the same time
- TRH: Tamper-resistant hardware helps prevent unauthorized access to the unit
- CW: Custom verbiage signs available on request

WARRANTY / LISTING:

- *5 year warranty on all electronics and housing. Battery pro rated for 5 years
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes
- UL Listed for wet locations (-4°F–122°F)

DIMENSIONS:



ORDERING INFORMATION

Example: "EW-1R-N-B-TRH-CW"

MODEL	No. of FACES		LETTER COLOR		BATTERY		HOUSING COLOR		OPTIONS	
EW	1	Single Face	R	Red	Α	AC Only	W	White	SD1	Self-diagnostics
	2	Double Face	G	Green	Ν	NiCad Battery	В	Black	TRH	Tamper Resistant Hardware
			•		•		G	Gray	2C ²	Dual circuit operation
NOTES							•		CW	Custom Wording

NOTES:

1. Available on NiCad exits only.

2. Available on AC only exits.

Specification is subject to change.

*Warranty does not apply to installation errors, natural disasters, and/or abuse.