



KEY FEATURES

ILLUMINATION:

- · Long lasting, efficient, ultra bright white LED lamp heads
- High performance chrome-plated metallic reflector and plastic lens standard with 8 LEDs providing 1 watt per head. Optional 12 LED's in each lamp head provide 1.5 watts per head
- Adjustable LED lamp heads increases center-to-center spacing

ELECTRICAL:

- Powered from low voltage power source with low voltage wiring (not provided)
- Multi-volt for use with 3.6V, 6V, 9.6V and 12V batteries

MOUNTING:

- Universal mounting base mounts to single-gang switch box
- Distance of maximum run is determined by system voltage, wire gauge and total maximum wattage on the run
- · Suitable for wall or ceiling mount


HOUSING:

- Available in both engineering grade, high-impact resistant thermoplastic or premium grade die-cast aluminum housing
- Sealed and gasketed in standard gray or optional black finish

WARRANTY / LISTING:

- *5 year warranty
- UL Listed
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes

DIMENSIONS:



ORDERING INFORMATION

Example: "LRHWP-1-P-G-SD-HL"

| MODEL | No. of HEADS | | HOUSING STYLE | | HOUSING COLOR | | OPTIONS | |
|-------|--------------|-------------|------------------|---------------|------------------|-------|---------|---|
| LRHWP | 1 | Single Head | Р | Thermoplastic | G | Gray | Blank | For Standard non-self-diagnostic fixtures |
| | 2 | Double Head | D | Die-cast | В | Black | SD | For use with fixtures with a self-diagnostic option |
| | | | | | | | HL | High Lumen 12 LEDs |

Specification is subject to change.

